FOG PROGRAM

SELF-CLEANING GREASE TRAPS AGREEMENT

Self- Cleaning Requirements/Procedures

Requirements:

- 1. The grease trap is no more than 50 gallons in liquid retention capacity;
- 2. Grease and floatable solids must be removed a minimum of once every seven (7) days and the entire contents of the grease trap is removed from the grease trap and baffles at a minimum of every 30 days, unless otherwise authorized by the District.
- 3. Date-stamped photo of empty grease trap (every 30 days, unless otherwise authorized by the District) to prove that job was completed effectively. Failure to provide pictures voids the cleaning record.
- 4. Signed and dated log, with amount of grease removed.

Correct Procedure for Self-Cleaning Your Grease Trap (Every 30 days, unless otherwise authorized by District)

- 1. Remove lid of the grease trap
- 2. Observe the manner in which the internal parts are installed because you'll have to reinstall them properly when you finish cleaning the trap.
- 3. Begin removing contents of the grease trap by dipping or vacuuming the waste products from the inside of the grease trap.
- 4. Remove all contents until grease trap is empty.
- 5. Do NOT use hot water, degreasers, or soaps to clean the interior of the trap.
- 6. Scrape all the inside walls, baffles, and screens to insure movement of water through unit.
- 7. Inspect and note condition of tank, baffle and all removable parts. Schedule repairs or replacement as needed.
- 8. Make sure the grease trap has been properly reassembled (all internal parts are in their proper place).
- 9. Examine the gasket for damage. Replace if necessary never use tube silicone as a gasket.
- 10. Clean and reinstall rubber gasket and reposition lid on tank. Ensure all screws and holdowns are in place and properly tightened.
- 11. Ensure enough absorbent material has been placed in bag to soak up all excess liquids. Add more if needed. Securely tie the bag of waste closed so that it does not leak.
- 12. Place bag in the garbage (solid waste) dumpster or designated receptacle. It is illegal to dump grease trap or kitchen waste into storm drains, ponds or outdoor areas.

I	of	, hereby agree to the above self-cleaning
procedures.		